

2.3" Four-Digit Process-Cycle Down Timer

DC-25T-DN-BCD

DC-Digital[™]
by IES Ltd.



Features

- Down timer from 99 minutes
- Displays minutes and seconds
- Durable aluminum case
- Key hole mounting
- 1-year warranty
- 2.3" super bright display
- Rotary switch preset
- Visible up to 120Ft.
- 90-240 volt AC power adapter
- Knockouts and terminal block
- 1-Input operation
- Made in USA

Options

- NEMA 4X Enclosure
- Custom configurable
- 12VDC Power
- End of period buzzer

Specifications

- **Display** Four digit; seven segment; red LED display
- **Case** Aluminum; 9.75"W x 4.75"H x 3.0"D
- **Weight** 5.0 pounds
- **Power Source** 100-240VAC at 50/60Hz UL listed power adapter
- **Operating Temp.** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Black powder coating

DC-Digital DC-25T-DN-BCD Process-Down Timer Description

The DC-Digital DC-25T-DN-BCD Cycle-Process Timer is designed to time highly repetitive procedures. Separate controls for the technician and operator provide process control and convenience respectively. Top mounted rotary switches provide a simple, permanent way to program the cycle-process time. With one input, the timer resets to the set value and counts down to zero. Use the Cycle-Process Timer to time chemical baths, ovens, dryers, lamp exposure, curing, assembly milestones, service deadlines etc. The DC-25T-DN-BDC comes with terminals and knockouts for field wiring, a polycarbonate lens, aluminum case with keyhole mounts. This equipment is proudly made in USA. This display is factory serviceable.

DC-25T-DN-BCD Rear View

