

DC-Digital

Operating and installation instructions for the DC-806T-UP-Seconds



Description:


- **The DC-806T-UP-Seconds, is a Made in the U.S.A, outdoor rated, 8.0 inch, 6 digit, Red LED, up timer.**
- Power: Entire display requires a 100-240VAC, 50/60 hertz, 15 amp with ground outlet (supplied by end user). Power cord is 9ft. SJE00W, 3 prong, 300 volt.
- Time interval: Counts up to 9999 seconds and 99 hundredths. Always shows hundredths, tenths, Seconds, Seconds, Seconds, Seconds.
- Time base: Crystal Oscillator +/- 2 minutes per year (factory calibrated)
- Mounting: Wall mount using the adjustable (4) keyhole tabs
- Weight: 40 lbs.
- Viewing distance: up to 400ft.
- Enclosure: All aluminum .080inch thick, 11.125 inches high x 36.5 inches wide x 3.25 inches deep.
- Paint: Black textured (finger print resistant) powder coat finish.
- Controls: (2) wired remote momentary pushbuttons for **Start, Stop, Reset to Zero** with 100feet of cabling (RJ45 connectors, CAT5E orange, orange white), **Start** also has 2 feet of cabling with a 3.5mm male connector. Switch is double pole actuations with 60mm Red mushroom head (Part #'s actuator ZB4BR4, switch ZB4BZ103).

Connections: Make all proper connections before putting the DC-806T-UP-Seconds into operation.

- Connect both the **Start** and the **Stop** wired remote pushbuttons to the display. Use either of the provided RJ485 jacks located on both the left and the right sides.
- Plug the DC-806T-UP-Seconds into a standard 120VAC wall outlet. The DC-806T-UP-Seconds will display 0000.00.

Operating the timer:

- **Starting the timer:** Press and release the **Start** pushbutton. This will cause the timer to start counting up. Note: The **Start** pushbutton comes equipped with an auxiliary equipment contact closure N.O (normally open) output that has a 3.5mm mono jack.
- **Stopping the timer:** Press and release the **Stop** pushbutton. This will cause the timer to stop and hold the timer value.
- **Resetting the timer to Zero:** Press and release the **Stop** or the **Start** pushbutton. This will cause the timer to reset the value to zero's.



- **Mounting:** See drawing above. Mount the DC-806T-UP-Seconds, Display in clean dry dust free area. There are (3) teardrop mounting tabs for easy wall or frame hanging using screws secured to a wall or frame (mounting screws not included). Note: The teardrop mounting tabs adjust wider or narrower by loosening their respective set screw and sliding it along the enclosure channel.

For further questions please contact Industrial Electronic Service D.B.A. DC-Digital @ 937-746-9750 or visit us @ www.dc-digital.com.