

15 inch Four-Digit Countdown timer with top mounted controls

[DC-150T-DN-IN](#)

DC-Digital
tm



Features

- Counts down from 99 min to hundredths of a second
- All Extruded aluminum enclosure
- Displays down to 100ths of a second
- 1-Year warranty
- Top mounted tactile pushbutton controls
- Factory calibrated quartz accuracy
- Large 15 Inch Super Bright Bar LED's
- Outdoor rated
- Visible up to 750Ft.
- Factory serviceable modular design

Options

- BCD Rotary Set Switches
- Wired or wireless remote control
- Green, Amber LED available
- Static Display, Timer, Temperature available
- Hours and Minutes timing interval available
- EOP (end of period buzzer)

Specifications

- **Controls** Tactile momentary pushbuttons mounted on the top of the enclosure
(1) Start-Stop (pause), (1) Reset to the set value, (1) Reset to zero, (1) Set Hours,
(1) Set Minutes
- **Display** 15 Inch, four digit, seven segment, red LED display
- **Case** Aluminum, 48"W x 18.5"H x 3.25"D
- **Weight** 35.0 Pounds
- **Power Source** 120-250 VAC, 50-60 Hz, @ 3 amps, outdoor rated junction box.
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Black Powder Coating

[DC-150T-DN-IN](#) Description

The DC-Digital [DC-150T-DN-IN](#) is designed to be used where a highly visible countdown timer is needed. The [DC-150T-DN-IN](#) utilizes the **shift digit technology** that allows the user to see minutes as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in industry, government, schools and churches. It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tough powder coated enclosure gives it a professional look that will hold up in many harsh environments.

DC-150T-DN-IN Mounting and Dimensions

There are (2) aluminum .125 inch x 1.5 inch x .75 inch C channel mounting rails that can be used as mounting brackets and secured to a wall or they can be removed and the (4) 5/16 x 1 inch bolts can be used.

