15.0 inch Six-Digit **RF** wirelessly controlled Time of Day Clock DC-156S-W-IN



Features

- Time of Day 12-24 Hour Format
- All aluminum enclosure (Black powder coated)
- Surface mount
- 1 year Warranty
- RF-Wireless handheld controller (150' range, WRC-2T)



- + or 2 minutes per year accuracy (factory calibrated)
- Large 15.0 Inch Super Bright LED's
- Junction Box for 1/2 Inch conduit (power)
- Visible up to 750Ft.

Computer controlled

Factory serviceable modular design •

Network or GPS Atomic Updates

Timer, Counter, Static number display

Options

- Hours and minutes set switches mounted on the top of the enclosure
- NEMA 4X Polycarbonate case
- Double face hall mount
- Yellow or Green LEDs

Specifications

Input 2 Function Membrane Switch Pushbutton, 2.4Ghz RF Wireless 1mW •

•

- 15 Inch, six digit, seven segment, red LED display Display
- Extruded aluminum enclosure, 72"W x 19"H x 3-1/4"D Case
- Weight 35.0 Pounds
- Power Source 120-250 VAC, 50-60 Hz,@ 3 amps with ground (junction box with pigtails)
- 0° to 49° Celsius (32° to 120° Fahrenheit) **Operating Temp** •
- **Case Finish Black Powder Coating**

DC-156S-W-IN Description

The DC-Digital DC-156S-W-IN is designed to be used where a Large time of day clock is needed. The flexibility of this unique design gives it a broad range of applications in schools, industry, governmental and churches. It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tough powder coated enclosure gives it a professional look that will hold up in many harsh environments. This equipment is proudly made in the USA. This display is factory serviceable.

DC-156S-W-IN Mounting and Dimensions

There are (2) aluminum .125 inch x 1.5 inch x .75 inch C channel mounting rails that can be used as mounting brackets and secured to a wall or they can be removed and the (4) $5/16 \times 1$ inch bolts can be used.

