

2.3 inch Four-Digit RF Wireless Digital Red LED Time of Day Clock [DC-25S-W](#)

DC-Digital
tm



Features

- Time of Day 12-24 Hour Format
- 14 Ga. aluminum enclosure (Black powder coated)
- Mounts on 2 x 4 or 4 x 4 electrical box or on wall
- 1 year Warranty
- RF-Wireless handheld controller (150' range, WRC-2T)
- Visible up to 120Ft
- Large 2.3 Inch Red Super Bright LED's
- Made in the USA
- + or - 2 minutes per year accuracy (Factory calibrated)
- Factory Serviceable

Options

- Nema 4X IP66, IK08 rated enclosure
- Network, NTP controlled
- GPS or computer controlled
- Green LED's
- Flush Mount
- More options call 800-977-6872
- Add a Count up Timer or Countdown Timer

Specifications

- **Input** 2 Function Membrane Switch Pushbutton, 2.4Ghz RF Wireless 1mW
- **Display** Four digit bar; high intensity; seven segment; red LED display
- **Case** All aluminum enclosure, 9.625"W x 4.625"H x 3"D
- **Weight** 5.0 Pounds
- **Power Source** 4 Watts; 90 – 240VAC 50/60 Hz, 3 Prong with ground 6 ft. power cord
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Tough Finger Print Resistant Black Textured Powder Coating

[DC-25S-W](#)

The DC-Digital [DC-25S-W](#) wireless is designed to be used where a Large time of day clock is needed. The flexibility of this unique design gives it a broad range of applications in schools, industry, governmental and churches. It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tough powder coated enclosure gives it a professional look that will hold up in many harsh environments.

DC-25S-W Mounting and Dimensions

There are (6) keyhole mounting knockouts for easy attachment to an electrical handy-box or an electrical 4 square box or simply use the (2) outer keyhole mounting knockouts and a couple of screws secured to a wall. Also supplied are 4 adhesive backed rubber feet that can be adhered to the enclosure bottom for table or Mount on a desk top.

