# 2.3 inch Four-Digit LED

Count Up Timer with Internal terminal blocks for controls

DC-25T-UP-Term





#### **Features**

- Counts up to 99 hours from hundredths of a second
- Heavy duty all aluminum enclosure
- Displays up to 100ths of a sec
- 1 year Warranty
- Terminal block connections for controls from PLC's, sensors, relays, switches etc.
- Visible up to 120Ft
- Large 2.3 Inch Super Bright LED's
- Made in the USA
- Shift Digit Technology
- Factory Serviceable

### **Options**

- Momentary push button switches
- Wired remote control
- Input redundancy, terminal block and switches
- 1-Switch for Start-Stop-Reset

- Nema 4X IP66, IK08 rated enclosure
- 24Vdc power
- 120 VAC 9 foot power cord
- 100s of options call 800-977-6872

## **Specifications**

Input (1) Start-Stop (pause), (1) Reset to Zero, 10ms response

Momentary contact closure, TTL, NPN or connection to 0V

Display
Four digit bar; high intensity; seven segment; red LED display

• Case All aluminum enclosure, 9.625"W x 4.625"H x 3"D

Weight 5.0 Pounds

Power Source
3 Watts; 90 – 240VAC 50/60 Hz (12VDC @ 700 ma power supply, PS-12-700)

Operating Temp 0° to 49° Celsius (32° to 120° Fahrenheit)

Case Finish Finger Print Resistant, Tough, Black Textured Powder Coating


## DC-25T-UP-Term

The DC-Digital DC-25T-UP-Term is designed to be used where a highly visible count up timer is needed. The DC-25T-UP-Term utilizes the **shift digit technology** that allows the user to see hours as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in industry, government, schools and churches. The Internal terminal blocks allow for hardwired controls from PLC's, switches, relays and or sensors. It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tough powder coated enclosure gives it a professional look that will hold up in many harsh environments.

Specification Sheet Page | 1

# **DC-25T-UP-Term** Mounting and Dimensions

There are (6) keyhole mounting knockouts for easy attachment to an electrical handy-box or an electrical 4 square box or simply several screws secured to the wall. Also supplied are 4 adhesive backed rubber feet that can be adhered to the enclosure bottom for table or desk top mounting.



Specification Sheet Page | 2