4.0 Inch Four-Digit Red LED

Digital counter, accepts multiple input and power types

DC-40C-Term





Features

- Counts up to 9999
- Heavy duty 14Ga. all aluminum enclosure
- Momentary Contact Closure or PNP source, 24V pulse
- Mechanical or Electronic Switch activation
- Terminal block connections for controls from PLC's, sensors, relays, switches etc.
- Visible up to 200Ft
- Large 4.0 Inch Super Bright LED's
- Made in the USA
- Factory Serviceable
- 1 year Warranty

Options

- Momentary push button switches
- Wired remote control
- Input redundancy, Terminal blocks for hardwire connections and switches mounted on top
- 24Vdc input pulse for count inputs

- Nema 4X IP66, IK08 rated enclosure
- 24Vdc power
- 120 VAC 9 foot power cord
- RF Wireless
- 100s of options call 800-977-6872

Specifications

• Input (1) Increment, (1) Decrement, (1) Reset to Zero, 10ms response

Momentary contact closure, PNP sourced pulse (5-30VDC), 24VDC pulse

Display
Four digit bar; high intensity; seven segment; red LED display

• Case 14Ga. All aluminum enclosure, 16.25"W x 6.75"H x 3"D

• Weight 6.0 Pounds

Power Source
Watts; 90 – 240VAC 50/60 Hz (12VDC @ 700 ma power supply, PS-12-700)or

customer supplied 24VDC@700mA, (Terminal block connection included

• Operating Temp 0° to 49° Celsius (32° to 120° Fahrenheit)

Case Finish
Finger Print Resistant, Tough, Black Textured Powder Coating

DC-40C-Term Description

The DC-Digital DC-40C-Term is designed to be used where a highly visible counter is needed. The flexibility of this unique design gives it a broad range of applications in industry, government, schools and churches. The Internal terminal blocks allow for hardwired controls from PLC's, switches, relays and or sensors that can provide a mechanical contact closure or a PNP sourced electronic switch action. It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tough powder coated enclosure gives it a professional look that will hold up in many harsh environments.

937-746-9750, Fax 937-746-9704

325 Industry Drive, Carlisle, OH

Copyright IES, LTD. 2009

Specification Sheet Page | 1

DC-40C-Term Mounting and Dimensions

There are (6) keyhole mounting knockouts for easy attachment to an electrical handy-box or an electrical 4 square box or simply several screws secured to the wall. Also supplied are 4 adhesive backed rubber feet that can be adhered to the enclosure bottom for table or desk top mounting.

