

4.0 inch Four-Digit LED Count Up Timer, accepts multiple input and power types

[DC-40T-UP-Term](#)

DC-Digital
tm



Features

- Counts up to 99 hours from hundredths of a second
- Heavy duty 14Ga. all aluminum enclosure
- Displays up to 100ths of a sec
- 1 year Warranty
- Terminal block connections for controls from PLC's, sensors, relays, switches etc.
- Visible up to 200Ft
- Large 4.0 Inch Super Bright LED's
- Made in the USA
- Shift Digit Technology
- Factory Serviceable

Options

- Momentary push button switches
- Wired remote control
- RF wireless remote control
- 1-Switch for Start-Stop-Reset
- Nema 4X IP66, IK08 rated enclosure
- 24Vdc power
- 120 VAC 9 foot power cord
- 100s of options call 800-977-6872

Specifications

- **Input** (1) Start-Stop (pause), (1) Reset to Zero, 10ms response
Momentary contact closure, PNP sourced pulse (5-30VDC), 24VDC pulse
- **Display** Four digit bar; high intensity; seven segment; red LED display
- **Case** 14Ga. All aluminum enclosure, 16.25"W x 6.75"H x 3"D
- **Weight** 6.0 Pounds
- **Power Source** 4 Watts; 90 – 240VAC 50/60 Hz (12VDC @ 700 ma power supply, [PS-12-700](#)) or customer supplied 24VDC@700mA, (Terminal block connections included)
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Finger Print Resistant, Tough, Black Textured Powder Coating

[DC-40T-UP-Term](#)

The DC-Digital [DC-40T-UP-Term](#) is designed to be used where a highly visible count up timer is needed. The [DC-40T-UP-Term](#) utilizes the **shift digit technology** that allows the user to see hours as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in industry, government, schools and churches. The Internal terminal blocks allow for hardwired controls from PLC's , switches, relays and or sensors. It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tough powder coated enclosure gives it a professional look that will hold up in many harsh environments.

DC-40T-UP-Term Mounting and Dimensions

There are (6) keyhole mounting knockouts for easy attachment to an electrical handy-box or an electrical 4 square box or use the (2) outer keyhole mounting knockouts and mount to several screws secured to the wall. Also supplied are 4 adhesive backed rubber feet that can be adhered to the enclosure bottom for table or desk top mounting.

