8.0 inch Six-Digit

Digital Red LED Time of Day Clock (outdoor)

DC-806S



Features

- Time of Day 12-24 Hour Format
- All aluminum enclosure (Black powder coated)
- Surface mount
- 1 year Warranty
- Hours and minutes set switches mounted on the top of the enclosure.



- + or 2 minutes per year accuracy (factory calibrated)
- Large 8.0 Inch Super Bright LED's
- Junction Box for 1/2 Inch conduit (power)
- Visible up to 400Ft.
- Factory serviceable modular design

Options

- RF Wireless remote controls
- NEMA 4X Polycarbonate case
- Double face hall mount
- Yellow or Green LEDs

- Network or GPS Atomic Updates
- Timer, Counter, Static number display
- Computer controlled
- RF Wireless System

Specifications

- Input 2) Momentary sealed pushbutton switches; Set Hours, Set Minutes, Set Format
 - **Display** 8.0 Inch, Six digit, Seven Segment, High Intensity, Red LED display
- Case Extruded Aluminum; 11.125 inches high x 36.5 inches wide x 5.5 inches deep.
- Weight 35.0 Pounds
- **Power Source** 28 Watts; 100 240VAC 50/60 Hz, 2 wire with ground pigtails in junction box (9 volt rechargeable battery backup included)
- Operating Temp 0° to 49° Celsius (32° to 120° Fahrenheit)
- Case Finish Tough, Finger Print Resistant, Black Powder Coating

DC-806S Description

The DC-Digital <u>DC-806S</u> is designed to be used where a Large time of day clock is needed. The flexibility of this unique design gives it a broad range of applications in schools, industry, governmental and churches. It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tough powder coated enclosure gives it a professional look that will hold up in many harsh environments. This equipment is proudly made in the USA. This display is factory serviceable.

1 1														
1 1	0000	0000000		0000000		0000000		0000000		0000000		0000000		
1 1	0000	00000	0000	00000		000000	000	000000	000		0000000	0.04	0000	00000
1 1		00	00	00		00	00	00	00		00	00		00
1 1	00 00	00	00		00		00	00		00		00	00	00
1 1	00	00	00		00		00	00		00		00	00	00
1 1	5ŏ	00	00	00		00	00	ŏŏ	õõ		ŏŏ	ŏŏ	00	ŏŏ
1 1	00	00	00			0.0	0.0	00					00	
	00000	00000	0,000	80000		000000	0.0		0,00		000000	0,0		0,00
	00000	00000	00000	0,000		0,0000	000	000000	0,000		000000	000	00000	0,004
1 1	00	00	00	00		00	00	00	00		00	00	00	00
1 1	00	00	00	00	00	00	00	00	00	00	00	00	00	00
1 1	00	00	00		00		00	00		00		00	00	00
1 1	00	õõ	őő	00	00	ŏŏ	õõ	őő	ŏŏ		őő	ŏŏ	00	00
1 1														
1 1	0000000	0000	0000	00000		000000	000	000000	000		0000000	000	00000	000
	0000 00 1	0000	0000	0000		00000	00	00000	000		00000	00	0000	004

