

# 15 inch Four-Digit Count up timer with top mounted controls

[DC-150T-UP-IN](#)

**DC-Digital**  
tm



## Features

- Counts up to 99 hours from hundredths of a second
- All Extruded aluminum enclosure
- Displays down to 100ths of a second
- 1-Year warranty
- Top mounted tactile pushbutton controls
- Factory calibrated quartz accuracy
- Large 15 Inch Super Bright Bar LED's
- Factory serviceable modular design
- Visible up to 750ft.

## Options

- Terminal block connections
- Wired remote control
- RF wireless remote
- 1-Switch for Start-Stop-Reset
- Input redundancy, terminal blocks and switches
- Nema 4X IP66, IK08 rated enclosure
- 24VDC power input
- 100s of options call 800-977-6872

## Specifications

- **Controls** (1) Start-Stop (pause), (1) Reset to Zero, Momentary Pushbutton
- **Display** 15 Inch, four digit, seven segment, red LED display
- **Case** Aluminum, 48"W x 18.5"H x 3.25"D
- **Weight** 35.0 Pounds
- **Power Source** 120-250 VAC, 50-60 Hz, @ 3 amps, outdoor rated junction box.
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Black Powder Coating

## [DC-150T-UP-IN](#) Description

The DC-Digital [DC-150T-UP-IN](#) is designed to be used where a highly visible count up timer is needed. The [DC-150T-UP-IN](#) utilizes the **shift digit technology** that allows the user to see minutes as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in industry, government, schools and churches. It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tough powder coated enclosure gives it a professional look that will hold up in many harsh environments.

## DC-150T-UP-IN Mounting and Dimensions

There are (2) aluminum .125 inch x 1.5 inch x .75 inch C channel mounting rails that can be used as mounting brackets and secured to a wall or they can be removed and the (4) 5/16 x 1 inch bolts can be used.

