

15 inch Six-Digit Red LED Countdown Timer with RF wireless controls (outdoor)

[DC-156T-DN-W](#)

DC-Digital
tm



Features

- Counts down from 99 hours, 59 Minutes, 59 seconds
- All Extruded IP66 Rated aluminum enclosure
- Excellent viewing in bright sunlight
- RF Wireless controls (150 ft. Range)
- Weatherproof outdoor junction box for connections
- Factory calibrated quartz accuracy
- Large 15 inch red LED's
- Outdoor rated sunlight rated
- Visible up to 750Ft.
- Factory serviceable modular design
- 1-Year warranty

Options

- Momentary push button switches
- Battery powered
- Green, Amber LED available
- Static Display, Temperature available
- 1- Switch Start-Stop-and-Reset
- Shift digit technology
- EOP (end of period buzzer)
- Flashing on count back up mode

Specifications

- **Controls** 6 Button Handheld RF Wireless Remote Control, 2.4Ghz RF Wireless 1mW, (150 ft. range); Start Stop, Reset to Last Value, Reset to Zero, Set Hours, Set Minutes, Set Seconds.
- **Display** Four digit bar; high intensity; seven segment; red LED display
- **Case** All aluminum, IP 66 outdoor, wet location, waterproof enclosure; 72 inches Wide x 18 inches High x 3 inches Deep
- **Weight** 50.0 Pounds
- **Power Source** 480 Watts; 90 – 240VAC 50/60 Hz @ 4 amps, outdoor rated junction box with pigtails
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Black Textured Powder Coating

[DC-156T-DN-W](#) Description

The DC-Digital [DC-156T-DN-W](#) is designed to be used where a wireless 6 digit outdoor countdown timer is needed. The RF (Radio Frequency) wireless control gives the user easy access and total freedom to all of its functions. The high intensity LED's make easy viewing in bright sunlight conditions. Long viewing distances are accomplished with its large red LED display. The all aluminum, IP66 wet location , water proof, outdoor rated, black extra tuff powder coated enclosure gives it a professional look that will hold up in many harsh environments. This unit includes one wireless remote control ([WRC-6T](#)). Additional wireless controllers are available for purchase.

DC-156T-DN-W Mounting and Dimensions

There are (2) aluminum .125 inch x 1.5 inch x .75 inch C channel mounting rails that can be used as mounting brackets and secured to a wall or they can be removed and the (4) 5/16 x 1 inch bolts can be used.

