

## 2.3 inch Six-Digit Network Time of Day Clock

[DC-256N](#)

**DC-Digital**  
tm



### Features

- Atomic Time from Network (DHCP or Static IP)
- Time Zone Selectable
- Surface mountable on 2 x 4 or 4 x 4 Electrical
- Durable finger print resistant aluminum case
- Made in the USA
- 12-24 Hour Atomic Time NTP or SNTP
- Large 2.3 Inch Super Bright Bar LED's
- 1/2 inch Knockouts on 3 sides
- Visible up to 120Ft.
- Factory serviceable modular design

### Options

- POE injector
- NEMA 4X Polycarbonate case
- Double face hall mount
- Network, POE
- Static Display, Timer, Temperature available

### Specifications

- **Input** Data DHCP or Static IP NTP or SNTP
- **Display** 2.3 Inch, Six digit, Seven Segment, Red LED display
- **Case** Extruded Aluminum; 12.875"W x 5.75"H x 2.25"D
- **Weight** 7.0 Pounds
- **Power Source** 5 Watts; 90 – 240VAC 50/60 Hz (12VDC @ 700 ma power supply, [PS-12-700](#))
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Tough, Finger Print Resistant, Black Powder Coating
- **Cabling** Ethernet

### [DC-256N](#) Description

The DC-Digital [DC-256N](#) time of day clock is designed to be used in any application where any 6 digit time of day clock is needed to be seen. It automatically queries NTP once every 10 seconds and on power up. It can be set up for 12 or 24 hour time format (default is 12 Hour). It can be set up for static IP to receive the NTP from your server (default is DHCP). This unique design can be used in either existing buildings or new construction. The [DC-256N](#) time of day clock comes with an aluminum case, polycarbonate lens, and keyhole mounting brackets. This equipment is proudly made in the USA. This display is factory serviceable.

## [DC-256N](#) mounting and Dimensions

There are (2) adjustable teardrop tabs for mounting the [DC-256N](#) to a wall. Note: The teardrop mounting tabs adjust wider or narrower by loosening their respective set screw and sliding it along the enclosure channel.

