

# 2.3 inch Six-Digit

Count Up timer with RF wireless controls

[DC-256T-UP-W](#)



## Features

- Counts up to 99 hours
- RF Wireless controls (150' range, WRC-2T)
- Additional timers can be used in the same area (Multiple channels)
- All aluminum enclosure
- 1 year Warranty
- Visible up to 120Ft
- Large 2.3 Inch Super Bright LED's
- Shift Digit Technology (displays 100th of a second)
- Made in the USA
- Factory Serviceable

## Options

- Multi-Function Timer
- Additional channels available
- Nema 4X IP66, IK08 rated enclosure
- Higher power RF Wireless controls
- 120 VAC 9 foot power cord
- Hardwired remote controls
- Relay output end of period
- 100s of options call 800-977-6872

## Specifications

- **Input** 2 Function Membrane Switch Pushbutton (Start-Stop and Reset to Zero) , 2.4Ghz RF Wireless 1mW Handheld controller.
- **Display** 2.3 Inch, Six digit, Seven Segment, Red LED display
- **Case** Extruded Aluminum; 12.875"W x 5.75"H x 2.25"D
- **Weight** 7.0 Pounds
- **Power Source** 5 Watts; 90 – 240VAC 50/60 Hz (12VDC @ 700 ma power supply, [PS-12-700](#))
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Tough, Finger Print Resistant, Black Powder Coating

## [DC-256T-UP-W](#) Description

The DC-Digital [DC-256T-UP-W](#) is designed to be used where a wireless controlled count up timer is needed. The [DC-256T-UP-W](#) utilizes the **shift digit technology** that allows the user to see hours as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in schools, industry, governmental and churches. The RF (**R**adio **F**requency) wireless controllability gives the user easy access and total freedom to all of its functions without sacrificing limited control, as found in our competitors IR (Infrared Led) remotes (IR remotes have limited range of transmission 50 feet or less and is limited to indoor operation only). It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tuff powder coated enclosure gives it a professional look that will hold up in many harsh environments. This unit includes one wireless remote control (WRC-2T). Additional wireless controllers are available for purchase.

## DC-256T-UP-W mounting and Dimensions

There are (2) adjustable teardrop tabs for mounting the DC-256T-UP-W to a wall. Note: The teardrop mounting tabs adjust wider or narrower by loosening their respective set screw and sliding it along the enclosure channel.

