2.3 inch Six-Digit LED

Wireless Universal Countdown and Count Up Timer and Clock

<u>DC-256UTW</u>



Features

- All aluminum enclosure
- Counts up or down to 99:59:59
- Displays up to 100ths of a sec
- 1 year Warranty
- RF Wireless controls (150' range, WRC-8T)

Options

- High output end of period buzzer
- Wired remote control
- Nema 4X IP66, IK08 rated enclosure
- Higher power RF Wireless controls

- Visible up to 120Ft
- Large 2.3 Inch Super Bright LED's
- Made in the USA

•

•

- Shift Digit Technology
- Factory Serviceable
 - 120 VAC 9 foot power cord
- Hardwired controls
- Relay output end of period
- 100s of options call 800-977-6872

Specifications

- Controls 8 Function Membrane Switch Pushbutton, 2.4Ghz RF Wireless 1mW
 Display Six digit bar; high intensity; seven segment; red LED display
 Case Extruded Aluminum; 12.875"W x 5.75"H x 2.25"D
 Weight 7.0 Pounds
 - Power Source 4 Watts; 90 240VAC 50/60 Hz (12VDC @ 700 ma power supply, <u>PS-12-700</u>)
- Operating Temp 0° to 49° Celsius (32° to 120° Fahrenheit)
- Case Finish Black Textured Powder Coating

DC-256UTW

•

The DC-Digital <u>DC-256UTW</u> is designed to be used where a universal count up, countdown, timer and time of day clock is needed. The <u>DC-256UTW</u> utilizes the **shift digit technology** that allows the user to see hours as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in schools, industry, governmental and churches. The RF (**R**adio **F**requency) wireless controllability gives the user easy access and total freedom to all of its functions without sacrificing limited control, as found in our competitors IR (Infrared Led) remotes (IR remotes have limited range of transmission 50 feet or less and is limited to indoor operation only). It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tuff powder coated enclosure gives it a professional look that will hold up in many harsh environments. This unit includes one wireless remote control (<u>WRC-8T</u>). Additional wireless controllers are available for purchase.

937-746-9750, Fax 937-746-9704 325 Industry Drive, Carlisle, OH



DC-256UTW Mounting and Dimensions

There are (2) adjustable teardrop tabs for mounting the <u>DC-256UTW</u> to a wall. Note: The teardrop mounting tabs adjust wider or narrower by loosening their respective set screw and sliding it along the enclosure channel.

