

## 2.3 inch Four-Digit Red LED WIFI Network Time of Day Clock

[DC-25N-WIFI](#)

**DC-Digital**  
tm



### Features

- Wireless (WIFI) Atomic Time from Network
- Time Zone Selectable
- Surface mountable on 2 x 4 or 4 x 4 Electrical
- DHCP or Static IP Selectable
- Made in the USA
- 12-24 Hour Atomic Time NTP or SNTP
- Large 2.3 Inch Super Bright Bar LED's
- 1/2 inch Knockouts on 3 sides
- Visible up to 120Ft.
- Factory serviceable modular design

### Options

- POE injector
- NEMA 4X Polycarbonate case
- Double face hall mount
- POE injector
- Network, POE
- Static Display, Timer, Temperature available
- Network, POE

### Specifications

- **WIFI Adapter: Input** Dual Band 2.4 or 5 GHz 802.11 b/g/n/AP/ Gateway/Router, Protected Access (WPA2-PSK, WPA-PSK and WEP data encryption)
- **Network Card: Input** Data DHCP or Static IP NTP or SNTP
- **Display** Four digit bar; high intensity; seven segment; red LED display
- **Case** All aluminum enclosure, 9.625"W x 4.625"H x 3"D
- **Weight** 5.0 Pounds
- **Power Source** 4 Watts; 90 – 240VAC 50/60 Hz, 3 Prong with ground 6 ft. power cord
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Tough Finger Print Resistant Black Textured Powder Coating
- **Cabling** Ethernet

### [DC-25N-WIFI](#) Description

The DC-Digital [DC-25N-WIFI](#) time of day clock is designed to be used in any application where any 4 digit wireless network time of day clock is needed to be seen. It automatically queries NTP once every 10 seconds and on power up. It can be set up for 12 or 24 hour time format (default is 12 Hour). It can be set up for DHCP or static IP (default is DHCP) to receive the NTP from your server or from a predetermined server that outputs NTP. This unique design can be used in either existing buildings or new construction. The [DC-25N-WIFI](#) time of day clock comes with an aluminum case, polycarbonate lens, and keyhole mounting brackets. This equipment is proudly made in the USA. This display is factory serviceable.

## DC-25N-WIFI Mounting and Dimensions

There are (6) keyhole mounting knockouts for easy attachment to an electrical handy-box or an electrical 4 square box or simply use the (2) outer keyhole mounting knockouts and a couple of screws secured to a wall. Also supplied are 4 adhesive backed rubber feet that can be adhered to the enclosure bottom for table or Mount on a desk top.

