2.3 inch Four-Digit LED

Count Up Timer with Top
Mounted Pushbutton Controls

DC-25T-UP





Features

- Counts up to 99 hours from hundredths of a second
- 2 Tactile momentary pushbuttons
- Heavy duty all aluminum enclosure
- 1 year Warranty

- Visible up to 120 Ft.
- Large 2.3 Inch Super Bright LED's
- Made in the USA
- Shift Digit Technology
- Factory Serviceable

Options

- Terminal block connections
- Wired remote control
- RF wireless remote
- 1-Switch for Start-Stop-Reset

- Input redundancy, terminal blocks and switches
- Nema 4X IP66, IK08 rated enclosure
- 24VDC power input
- 100s of options call 800-977-6872

Specifications

Input (1) Start-Stop (pause), (1) Reset to Zero, Momentary Pushbutton
 Display Four digit bar; high intensity; seven segment; red LED display
 Case All aluminum enclosure, 9.625"W x 4.625"H x 3"D

Weight 5.0 Pounds

• Power Source 3 Watts; 90 – 240VAC 50/60 Hz, 6ft 3-prong power cord

• Operating Temp 0° to 49° Celsius (32° to 120° Fahrenheit)

Case Finish
 Finger Print Resistant , Tough, Black Textured Powder Coating

DC-25T-UP

The DC-Digital DC-25T-UP is designed to be used where a highly visible count up timer is needed. The DC-25T-UP utilizes the **shift digit technology** that allows the user to see hours as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in industry, government, schools and churches. It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black, extra tough powder coated enclosure gives it a professional look that will hold up in many harsh environments.

Specification Sheet Page | 1

DC-25T-UP Mounting and Dimensions

There are (6) keyhole mounting knockouts for easy attachment to an electrical handy-box or an electrical 4 square box or simply several screws secured to the wall. Also supplied are 4 adhesive backed rubber feet that can be adhered to the enclosure bottom for table or desk top mounting.

