

2.3 inch Four-Digit Digital LED
RF Wireless Controlled Count Up
Timer with Nema 4X, IP66 Rated,
Polycarbonate Enclosure

DC-25T-UP-W-Nema

DC-Digital
tm



Features

- Counts up to 99 hours
- RF Wireless controls (150' range, WRC-2T)
- Additional timers can be used in the same area (Multiple channels)
- Nema 4X, IP66, Corrosion Resistant Poly Enclosure
- 1 year Warranty
- Visible up to 120Ft
- Large 2.3 Inch Super Bright LED's
- Shift Digit Technology (displays 100th of a second)
- Made in the USA
- Factory Serviceable

Options

- Multi-Function Timer
- Additional channels available
- 14Ga. aluminum
- Higher power RF Wireless controls
- 120 VAC 9 foot power cord
- Hardwired remote controls
- Relay output end of period
- 100s of options call 800-977-6872

Specifications

- **Controls** 2 Function Membrane Switch Pushbutton (Start-Stop and Reset to Zero) , 2.4Ghz RF Wireless 1mW Handheld controller.
- **Display** Four digit bar; high intensity; seven segment; red LED display
- **Case** Poly Carbonate, IP66, Nema 4X, 9.5"W x 6.3"H x 3.5"D
- **Weight** 5.0 Pounds
- **Power Source** 4 Watts; 90 – 240VAC 50/60 Hz (12VDC @ 700 ma power supply, [PS-12-700](#))
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** White Enclosure Clear see through Lid

DC-25T-UP-W-Nema Description

The DC-Digital [DC-25T-UP-W-Nema](#) is designed to be used where a wireless controlled count up timer is needed. The [DC-25T-UP-W-Nema](#) utilizes the **shift digit technology** that allows the user to see hours as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in schools, industry, governmental and churches. The RF (**R**adio **F**requency) wireless controllability gives the user easy access and total freedom to all of its functions without sacrificing limited control, as found in our competitors IR (Infrared Led) remotes (IR remotes have limited range of transmission 50 feet or less and is limited to indoor operation only). It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The Nema 4X IP66, IK08 rated enclosure gives it a professional look that will hold up in many harsh environments. This unit includes one wireless remote control (WRC-2T). Additional wireless controllers are available for purchase.

DC-25T-UP-W-Nema Mounting and Dimensions

There are (4) .18 inch diameter mounting holes located at each corner underneath the clear lid. To access the mounting holes first remove the lid.

