4.0 inch Six-Digit LED

Count up timer with RF wireless controls

DC-406T-UP-W





Features

- Counts up to 99:59:59
- Heavy duty extruded aluminum enclosure
- Battery backup memory
- 1 year Warranty
- RF Wireless

- Visible up to 200Ft
- Large 4.0 Inch Super Bright LED's
- Made in the USA
- Displays Hours, Minutes, seconds
- Factory Serviceable

Options

- 2.3, 6.0, 8.0, 15 and 30 inch digit height
- Countdown
- Remote start stop
- Top mounted sealed pushbutton controls

- 120Vac, 9 ft. power cord
- 24Vdc power

Specifications

• Controls 2 Function Membrane Switch Pushbutton (Start-Stop and Reset to Zero),

2.4Ghz RF Wireless 1mW Handheld controller.

Display Six digit bar; high intensity; seven segment; red LED display
Case Extruded aluminum enclosure, 24.5"W x 7.75"H x 2.25"D

Weight 8.0 Pounds

• Power Source 4 Watts; 90 – 240VAC 50/60 Hz, 6ft 3-prong power cord

Operating Temp 0° to 49° Celsius (32° to 120° Fahrenheit)

• Case Finish Black Textured Powder Coating

DC-406T-UP-W

The DC-Digital DC-406T-UP-W is designed to be used where a wireless controlled count up timer is needed. The DC-406T-UP-W utilizes the **shift digit technology** that allows the user to see hours as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in schools, industry, governmental and churches. The RF (Radio Frequency) wireless controllability gives the user easy access and total freedom to all of its functions without sacrificing limited control, as found in our competitors IR (Infrared Led) remotes (IR remotes have limited range of transmission 50 feet or less and is limited to indoor operation only). It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tuff powder coated enclosure gives it a professional look that will hold up in many harsh environments. This unit includes one wireless remote control (WRC-2T). Additional wireless controllers are available for purchase.

937-746-9750, Fax 937-746-9704

325 Industry Drive, Carlisle, OH

Copyright IES, LTD. 2009

Specification Sheet Page | 1

DC-406T-UP-W Mounting and Dimensions

There are (2) teardrop mountings for easy attachment to a couple of screws secured to a wall. Also supplied are 4 adhesive backed rubber feet that can be adhered to the enclosure bottom for table or Mount on a desk top.

