

6.0 inch Four-Digit System Secondary Time of Day Clock-2 Wire

[DC-60-2W-System](#)

DC-Digital
tm



Features

- Synchronized from a Network Master Clock, GPS-MI or EZ-Time Computer through a PS-24BD
- Only 2 wires required for Data and Power
- Surface mountable
- Durable finger print resistant aluminum case
- Made in the USA
- Atomic time accuracy
- Large 6.0 Inch Super Bright Bar LED's
- Junction Box with 1/2 inch conn.
- Visible up to 200Ft.
- Factory serviceable modular design

Options

- Wireless
- NEMA 4X Polycarbonate case
- Double face hall mount
- Countdown function 1-9 minutes

Specifications

- **Input** Data and Power: 2-wires, 24VDC low voltage level, DC-Digital Protocol, 18 gauge pigtail wiring out of the back of the enclosure
- **Display** 6.0 Inch, Four digit, Seven Segment, Red LED display
- **Case** Extruded Aluminum; 16.25"W x 6.75"H x 3.06"D
- **Weight** 10.0 Pounds
- **Power Source** 20 Watts, 15-27VDC (data and power on the same 2 wires, requires [PS-24BD](#))
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Tough, Finger Print Resistant, Black Powder Coating
- **Cabling** (2) 18 gauge 12 Inch (Red + and Black -) pigtail wires run to a junction box mounted on the side of the enclosure

[DC-60-2W-System](#) Description

The DC-Digital [DC-60-2W-System](#), system secondary time of day clock is designed to be used in any application where any 4 digit time of day clock that utilizes only 2 wires for both data and power is needed to be seen. It is automatically synchronized once every 10 seconds. It can be set up for 12 or 24 hour time format (default is 12 Hour). This unique design can be used in either existing buildings or new construction. The [DC-60-2W-System](#), system secondary time of day clock comes with an aluminum case and keyhole mounting brackets. This equipment is proudly made in the USA. This display is factory serviceable.

DC-60-2W-System mounting and Dimensions

There are (2) adjustable keyhole mounting tabs for easy attachment to a wall.

