

6.0 inch Six-Digit LED

Network Time of Day Clock

[DC-606N](#)



Features

- Atomic Time from Network (DHCP or Static IP)
- Time Zone Selectable
- Surface mountable on 2 x 4 or 4 x 4 Electrical
- Durable finger print resistant aluminum case
- Made in the USA
- 12-24 Hour Atomic Time NTP or SNTP
- Large 6.0 Inch Super Bright Bar LED's
- 1/2 inch Knockouts on 3 sides
- Visible up to 300Ft.
- Factory serviceable modular design

Options

- POE injector
- NEMA 4X Polycarbonate case
- Double face hall mount
- Higher power RF Wireless controls
- Network, POE
- Static Display, Timer, Temperature available
- 100s of options call 800-977-6872

Specifications

- **Controls** Data DHCP or Static IP NTP or SNTP
- **Display** Six digit bar; high intensity; seven segment; red LED display
- **Case** Extruded aluminum enclosure, 23-1/8"W x 7-1/2"L x 3-1/8"D
- **Weight** 8.0 Pounds
- **Power Source** 4 Watts; 90 – 240VAC 50/60 Hz, 6ft 3-prong power cord
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Black Textured Powder Coating

[DC-606N](#)

The DC-Digital [DC-606N](#) time of day clock is designed to be used in any application where any 6 digit time of day clock is needed to be seen. It automatically queries NTP once every 10 seconds and on power up. It can be set up for 12 or 24 hour time format (default is 12 Hour). It can be set up for static IP to receive the NTP from your server (default is DHCP). This unique design can be used in either existing buildings or new construction. The [DC-606N](#) time of day clock comes with an aluminum case, polycarbonate lens, and keyhole mounting brackets. This equipment is proudly made in the USA. This display is factory serviceable.

[DC-606N](#) Mounting and Dimensions

There are (2) teardrop mountings for easy attachment to a couple of screws secured to a wall. Also supplied are 4 adhesive backed rubber feet that can be adhered to the enclosure bottom for table or Mount on a desk top.

