

# 8.0 inch Four-Digit System Secondary Time of Day Clock- Indoor

## [DC-80-4W-System](#)



## Features

- Synchronized from a Network Master Clock, GPS-MI or EZ-Time Computer
- Only 2 Data wires required (junction box)
- Surface mount
- Durable finger print resistant aluminum case
- Made in the USA
- Atomic time accuracy
- Large 8.0 Inch Super Bright Bar LED's
- Junction Box for 1/2 Inch (Data-in)
- Visible up to 400Ft.
- Factory serviceable modular design

## Options

- Wireless
- NEMA 4X Polycarbonate case
- Double face hall mount
- 2-Wire Power and Data
- Countdown function 1-9 minutes

## Specifications

- **Input** Data: 2-wires, 9600 baud, 8N1, 24VDC low voltage level, DC-Digital Protocol, 22 gauge pigtail wiring inside junction box on the side of the enclosure
- **Display** 8.0 Inch, Four digit, Seven Segment, Red LED display
- **Case** Extruded Aluminum; 11 inches high x 25 inches wide x 3.25 inches deep.
- **Weight** 20.0 Pounds
- **Power Source** 28 Watts; 90 – 240VAC 50/60 Hz, 3 Prong, 6 foot Power cord
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Tough, Finger Print Resistant, Black Powder Coating
- **Cabling** (2) 22 gauge 12 Inch (white and green) pigtail wiring inside a junction box mounted on the side of the enclosure

## [DC-80-4W-System](#) Description

The DC-Digital [DC-80-4W-System](#), system secondary time of day clock is designed to be used in any application where any 4 digit time of day clock is needed to be seen. It is automatically synchronized once every 10 seconds. It can be set up for 12 or 24 hour time format (default is 12 Hour). This unique design can be used in either existing buildings or new construction. The [DC-80-4W-System](#), system secondary time of day clock comes with an aluminum case, polycarbonate lens, and keyhole mounting brackets. This equipment is proudly made in the USA. This display is factory serviceable.

# DC-80-4W-System Mounting and dimensions:

There are (2) adjustable keyhole mounting tabs for easy attachment to a wall.

