8.0 inch Six-Digit

Network Time of Day Clock DC-806N





Features

- Atomic Time from Network (DHCP or Static IP)
- Time Zone Selectable
- Surface mount
- Durable finger print resistant aluminum case
- Made in the USA

- 12-24 Hour Atomic Time NTP or SNTP
- Large 8.0 Inch Super Bright Bar LED's
- Junction box for power and network drop
- Visible up to 400Ft.
- Factory serviceable modular design

Options

- 4-Digit
- Wired remote control
- Nema 4X IP66, IK08 rated enclosure

- 120 Vac 9 ft. power cord
- Static Display, Timer, Temperature available
- High output end of period buzzer

Specifications

- Input
 Data DHCP or Static IP, NTP or SNTP
- **Display** 8.0 Inch, Six digit, Seven Segment, High Intensity, Red LED display
- Case Extruded Aluminum; 11.125 inches high x 36.5 inches wide x 5.5 inches deep.
- Weight 35.0 Pounds
- **Power Source** 28 Watts; 100 240VAC 50/60 Hz, 2 wire with ground (junction box with pigtails).
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- Case Finish Tough, Finger Print Resistant, Black Powder Coating
- Cabling Ethernet Cat 3 or 5

DC-806N Description

The DC-Digital <u>DC-806N</u> time of day clock is designed to be used in any application where any 6 digit network time of day clock is needed to be seen. It automatically queries NTP once every 10 seconds and on power up. It can be set up for 12 or 24 hour time format (default is 12 Hour). It can be set up for static IP to receive the NTP from your server (default is DHCP). This unique design can be used in either existing buildings or new construction. This equipment is proudly made in the USA and is factory serviceable.

	0000	0000000		_00000000		_00000000_		_00000000_		_0000000_		00 0000000		
	00000	00000	00000	00000		000000	000	000000	000		0000000	000	000000	00,00
	00	00	00	00		00	00	00	00		00	00	00	00
	80	00	ōō		00		00	00		00		ōō	00	00
	00	00	00	00	00	00	00	00	00	00	00	00	00	00
	00	00	00	00		00	00	00	00		00	00	0.0	00
	00	00	00	00		00	00	00	00		00	00	00	00
3	2200	000000000					3000000000			800000000		00 000000000 00000000		
		00000	00 00	00000		00000	000	00000	00		00000 0	õõ	0000 0	00
	00	00	00	00		00	00	00	00		00	00	00	00
	õõ	õõ	ŏŏ	õõ			õõ	ŏŏ	ŏŏ	00		ŏŏ	ŏŏ	ŏŏ
	00	00	00		00		00	00		00		00	00	00
	00	00	00	00		00	00	00	00		00	00	0.0	00
	0000000	0.0	0.0	000000		000000	0.0_	000000	0.0.		0000000	0.0_	000000	0.0_
		0000	0000	00000		000000	001	00000	000		0000000	00	000000	00

