

15 inch Four-Digit Countdown timer with RF wireless controls

[DC-150T-DN-W](#)

DC-Digital
tm



Features

- Counts down from 99 min to hundredths of a second
- All Extruded aluminum enclosure
- Displays down to 100ths of a second
- 1-Year warranty
- RF Wireless controls (150' range, [WRC-6T](#))
- Factory calibrated quartz accuracy
- Large 15 Inch Super Bright Bar LED's
- Outdoor rated
- Visible up to 750Ft.
- Factory serviceable modular design

Options

- BCD Rotary Set Switches
- Top mounted tactile pushbutton controls
- Green, Amber LED available
- Static Display, Timer, Temperature available
- Hours and Minutes timing interval available
- EOP (end of period buzzer)

Specifications

- **Controls** 6 Function Membrane Switch Pushbutton, (Start/Stop, Reset To Zero, Reset To Last Value, Set Hours, Set Minutes, Set Seconds) 2.4Ghz RF Wireless 1mW
- **Display** 15 Inch, four digit, seven segment, red LED display
- **Case** Aluminum, 48"W x 18.5"H x 3.25"D
- **Weight** 35.0 Pounds
- **Power Source** 120-250 VAC, 50-60 Hz, @ 3 amps, outdoor rated junction box.
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Black Powder Coating

[DC-150T-DN-W](#) Description

The DC-Digital [DC-150T-DN-W](#) is designed to be used where a wireless countdown timer is needed. The [DC-150T-DN-W](#) utilizes the **shift digit technology** that allows the user to see hours as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in schools, industry, governmental and churches. The RF (**R**adio **F**requency) wireless controllability gives the user easy access and total freedom to all of its functions without sacrificing limited control, as found in our competitors IR (Infrared Led) remotes (IR remotes have limited range of transmission 50 feet or less and is limited to indoor operation only). It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tuff powder coated enclosure gives it a professional look that will hold up in many harsh environments. This unit includes one wireless remote control (WRC-6T). Additional wireless controllers are available for purchase.

DC-150T-DN-W Mounting and Dimensions

There are (2) aluminum .125 inch x 1.5 inch x .75 inch C channel mounting rails that can be used as mounting brackets and secured to a wall or they can be removed and the (4) 5/16 x 1 inch bolts can be used.

