

15 inch Four-Digit Count up timer with RF Wireless controls

[DC-150T-UP-W-IN](#)

DC-Digital
tm



Features

- Counts up to 99 hours from hundredths of a second
- All Extruded aluminum enclosure
- Displays down to 100ths of a second
- 1-Year warranty
- RF Wireless controls (150' range, WRC-2T)
- Factory calibrated quartz accuracy
- Large 15 Inch Super Bright Bar LED's
- Factory serviceable modular design
- Visible up to 750ft.

Options

- Terminal block connections
- Wired remote control
- RF wireless remote
- 1-Switch for Start-Stop-Reset
- Input redundancy, terminal blocks and switches
- Nema 4X IP66, IK08 rated enclosure
- 24VDC power input
- 100s of options call 800-977-6872

Specifications

- **Controls** 2 Function Membrane Switch Pushbutton (Start-Stop and Reset to Zero) , 2.4Ghz RF Wireless 1mW Handheld controller.
- **Display** 15 Inch, four digit, seven segment, red LED display
- **Case** Aluminum, 48"W x 18.5"H x 3.25"D
- **Weight** 35.0 Pounds
- **Power Source** 120-250 VAC, 50-60 Hz,@ 3 amps, outdoor rated junction box.
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Black Powder Coating

[DC-150T-UP-W-IN](#) Description

The DC-Digital [DC-150T-UP-W-IN](#) is designed to be used where a wireless controlled count up timer is needed. The [DC-150T-UP-W-IN](#) utilizes the **shift digit technology** that allows the user to see hours as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in schools, industry, governmental and churches. The RF (**R**adio **F**requency) wireless controllability gives the user easy access and total freedom to all of its functions without sacrificing limited control, as found in our competitors IR (Infrared Led) remotes (IR remotes have limited range of transmission 50 feet or less and is limited to indoor operation only). It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tuff powder coated enclosure gives it a professional look that will hold up in many harsh environments. This unit includes one wireless remote control (WRC-2T). Additional wireless controllers are available for purchase.

DC-150T-UP-W-IN Mounting and Dimensions

There are (2) aluminum .125 inch x 1.5 inch x .75 inch C channel mounting rails that can be used as mounting brackets and secured to a wall or they can be removed and the (4) 5/16 x 1 inch bolts can be used.

