

2.3 Inch Four-Digit LED

Universal Countdown and Count
Up Timer and Time of Day Clock

[DC-25UT-Nema-4X](#)

DC-Digital
tm



Features

- Counts up or down to 99 hours
- Displays up to 100ths of a sec
- Nema 4X IP66, IK08 rated enclosure
- 1 year Warranty
- Tactile pushbutton controls mounted on top
- Visible up to 120Ft
- Large 2.3 Inch Super Bright LED's
- Made in the USA
- Shift Digit Technology
- Factory Serviceable

Options

- High output end of period buzzer
- Wireless remote control
- All aluminum enclosure that mounts to standard electrical 2 x 4 or 4 x 4 junction box
- Higher power RF Wireless controls
- 120 VAC 9 foot power cord
- Tripod mount
- Relay output end of period
- 100s of options call 800-977-6872

Specifications

- **Controls** Tactile pushbutton controls mounted on top of the enclosure: Start/Stop, Reset to last Value, Reset to zero, Clock/Timer, Count up/Countdown, Set Hours, Set Minutes
- **Display** Four digit bar; high intensity; seven segment; red LED display
- **Case** Poly Carbonate, IP66, Nema 4X, 9.5"W x 6.3"H x 3.5"D
- **Weight** 4.0 Pounds
- **Power Source** 3 Watts; 90 – 240VAC 50/60 Hz, 6ft 3-prong power cord
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** White Enclosure Clear see through Lid

[DC-25UT-Nema-4X](#) Description

The DC-Digital [DC-25UT-Nema-4X](#) is designed to be used where a universal count up, countdown, timer and time of day clock is needed. The [DC-25UT-Nema-4X](#) utilizes the **shift digit technology** that allows the user to see hours as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in schools, industry, governmental and churches. The top mounted controls give the user flexible and instant control at any time. It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tuff powder coated enclosure gives it a professional look that will hold up in many harsh environments.

DC-25UT-Nema-4X Mounting and Dimensions

There are (4) .18 inch diameter mounting holes located at each corner underneath the clear lid. To access the mounting holes first remove the lid.

