# 8.0 inch Four-Digit LED

Countdown timer with top mounted controls

DC-80T-DN-W







#### **Features**

- Counts down from 99 min to hundredths of a second
- All Extruded aluminum enclosure
- Displays down to 100ths of a second
- 1-Year warranty
- RF Wireless controls (150' range, <u>WRC-6T</u>

- Factory calibrated quartz accuracy
- Large 8 Inch Super bright LED's
- Factory serviceable modular design
- Visible up to 400Ft.

#### **Options**

- BCD Rotary Set Switches
- Top mounted tactile pushbutton controls
- Green, Amber LED available

- Static Display, Timer, Temperature available
- Hours and Minutes timing interval available
- EOP (end of period buzzer)

#### **Specifications**

• Input 6 Function Membrane Switch Pushbutton, (Start/Stop, Reset To Zero, Reset To

Last Value, Set Hours, Set Minutes, Set Seconds) 2.4Ghz RF Wireless 1mW

Display Four digit bar; high intensity; seven segment; red LED display

Case
Extruded aluminum enclosure, 25 inches wide x 11 inches tall x 3-1/4 inches

deep

Weight 15.0 Pounds

Power Source20 Watts; 90 – 240VAC 50/60 Hz, 6ft 3-prong power cord

• Operating Temp 0° to 49° Celsius (32° to 120° Fahrenheit)

Case Finish Finger Print Resistant, Tough, Black Textured Powder Coating

## DC-80T-DN-W

The DC-Digital DC-80T-DN-W is designed to be used where a wireless countdown timer is needed. The DC-80T-DN-W utilizes the **shift digit technology** that allows the user to see hours as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in schools, industry, governmental and churches. The RF (Radio Frequency) wireless controllability gives the user easy access and total freedom to all of its functions without sacrificing limited control, as found in our competitors IR (Infrared Led) remotes (IR remotes have limited range of transmission 50 feet or less and is limited to indoor operation only). It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tuff powder coated enclosure gives it a professional look that will hold up in many harsh environments. This unit includes one wireless remote control (WRC-6T). Additional wireless controllers are available for purchase.


937-746-9750, Fax 937-746-9704 325 Industry Drive, Carlisle, OH


Copyright IES, LTD. 2009

Specification Sheet Page | 1

### **DC-80T-DN-W** Mounting and Dimensions

There are (2) adjustable keyhole mounting tabs for easy attachment to a wall.





Specification Sheet Page | 2