

# 4.0 Inch Four-Digit RF Wireless System Multi- Function Timer Secondary DC-40UTW-W-Secondary



## Features

- RF Wirelessly Synchronized from a DC-Digital Master
- 1500 ft. range outdoor, 300 ft. indoor
- Surface mountable on 2 x 4 or 4 x 4 Electrical
- Durable finger print resistant aluminum case
- Made in the USA
- Displays exactly as master
- Large 4.0 Inch Super Bright Bar LED's
- 1/2 inch Knockouts on 3 sides
- Visible up to 200Ft.
- Factory serviceable modular design

## Options

- 4 Wire Data
- NEMA 4X Polycarbonate case
- Double face hall mount
- 120 Vac with pigtails out the back
- 2-Wire Power and Data
- Countdown function 1-9 minutes
- 7 Segment green, blue, or yellow displays

## Specifications

- **Input from Master** Data: RF Wireless, 900 Mhz, ISM Band, Frequency Hopping, 9600 baud, 8N1, DC-Digital Protocol, 1500 feet range
- **Display** 4.0 Inch, Four digit, Seven Segment, Red LED display
- **Case** Aluminum; 16.25"W x 6.75"H x 3.0"D
- **Weight** 6.0 Pounds
- **Power Source** 6 Watts; 90 – 240VAC 50/60 Hz (12VDC @ 700 ma power supply, [PS-12-700](#))
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Tough, Finger Print Resistant, Black Powder Coating
- **Cabling** None

## DC-40UTW-W-Secondary Description

The DC-Digital DC-40UTW-W-Secondary, synchronizes wirelessly to a designated master to display exactly the count up, countdown time or time of day clock. It is designed to be used in any application where any 4 digit system timer/time of day clock is needed to be seen. It is automatically synchronized once every 10ms. This unique design can be used in either existing buildings or new construction. The DC-40UTW-W-Secondary, comes with an aluminum case, polycarbonate lens, and keyhole mounting holes. This equipment is proudly made in the USA. This display is factory serviceable.

# DC-40UTW-W-Secondary mounting and Dimensions

There are (6) keyhole mounting knockouts for easy attachment to an electrical 2 x 4 handy-box or an electrical 4 x 4 square box .

