

2.3 inch Four-Digit LED Wireless Universal Countdown and Count Up Timer and Clock

DC-25UTW

DC-Digital
tm



Features

- All aluminum enclosure
- Counts up or down to 99 hours
- Displays up to 100ths of a sec
- 1 year Warranty
- RF Wireless controls (150' range, [WRC-8T](#))
- Visible up to 120Ft
- Large 2.3 Inch Super Bright LED's
- Made in the USA
- Shift Digit Technology
- Factory Serviceable

Options

- High output end of period buzzer
- Wired remote control
- Nema 4X IP66, IK08 rated enclosure
- Higher power RF Wireless controls
- 120 VAC 9 foot power cord
- Hardwired controls
- Relay output end of period
- 100s of options call 800-977-6872

Specifications

- **Controls** 8 Function Membrane Switch Pushbutton, 2.4Ghz RF Wireless 1mW
- **Display** Four digit bar; high intensity; seven segment; red LED display
- **Case** All aluminum enclosure, 9.625"W x 4.625"H x 3"D
- **Weight** 3.0 Pounds
- **Power Source** 4 Watts; 90 – 240VAC 50/60 Hz (12VDC @ 700 ma power supply, [PS-12-700](#))
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Black Textured Powder Coating

DC-25UTW

The DC-Digital [DC-25UTW](#) is designed to be used where a universal count up, countdown, timer and time of day clock is needed. The [DC-25UTW](#) utilizes the **shift digit technology** that allows the user to see hours as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in schools, industry, governmental and churches. The RF (**R**adio **F**requency) wireless controllability gives the user easy access and total freedom to all of its functions without sacrificing limited control, as found in our competitors IR (Infrared Led) remotes (IR remotes have limited range of transmission 50 feet or less and is limited to indoor operation only). It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tuff powder coated enclosure gives it a professional look that will hold up in many harsh environments. This unit includes one wireless remote control ([WRC-8T](#)). Additional wireless controllers are available for purchase.

DC-25UTW Mounting and Dimensions

There are (6) keyhole mounting knockouts for easy attachment to an electrical handy-box or an electrical 4 square box. Also supplied are 4 adhesive backed rubber feet that can be adhered to the enclosure bottom for table or Mount on a desk top. Note: when mounting the [DC-25UTW](#) allow enough room for 2.4 gigahertz top mounted antenna.

