# 6.0 inch Four-Digit LED

Countdown timer with RF wireless controls

DC-60T-DN-W







### **Features**

- Extruded aluminum enclosure
- Counts down from 99 hours to hundredths of a second
- Displays up to 100ths of a sec
- 1 year Warranty
- Time of day display
- RF Wireless controls (150' range, <u>WRC-6T</u>)

- Visible up to 300Ft
- Large 6.0 Inch Super Bright LED's
- Made in the USA
- Shift Digit Technology
- Factory Serviceable

#### **Options**

- Top mounted tactile pushbutton controls
- BCD Rotary Set Switches
- Input redundancy, terminal block and switches
- Minutes and Seconds

- Nema 4X IP66, IK08 rated enclosure
- 24Vdc power
- Hours and minutes timing interval
- 100s of options call 800-977-6872

### **Specifications**

• Controls 6 Function Membrane Switch Pushbutton, (Start/Stop, Reset To Zero, Reset To

Last Value, Set Hours, Set Minutes, Set Seconds) 2.4Ghz RF Wireless 1mW

Display
Case
Four digit bar; high intensity; seven segment; red LED display
Extruded aluminum enclosure, 16-1/8"W x 7-3/4"L x 3-1/4"D

Weight 8.0 Pounds

• Power Source 4 Watts; 90 – 240VAC 50/60 Hz, 6ft 3-prong power cord (Indoor only)

Operating Temp 0° to 49° Celsius (32° to 120° Fahrenheit)

• Case Finish Black Textured Powder Coating

#### DC-60T-DN-W

The DC-Digital DC-60T-DN-W is designed to be used where a wireless countdown timer is needed. The DC-60T-DN-W utilizes the **shift digit technology** that allows the user to see hours as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in schools, industry, governmental and churches. The RF (Radio Frequency) wireless controllability gives the user easy access and total freedom to all of its functions without sacrificing limited control, as found in our competitors IR (Infrared Led) remotes (IR remotes have limited range of transmission 50 feet or less and is limited to indoor operation only). It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tuff powder coated enclosure gives it a professional look that will hold up in many harsh environments. This unit includes one wireless remote control (WRC-6T). Additional wireless controllers are available for purchase.

937-746-9750, Fax 937-746-9704

325 Industry Drive, Carlisle, OH

Copyright IES, LTD. 2009

Specification Sheet Page | 1

## **DC-60T-DN-W** Mounting and Dimensions

There are (2) teardrop mountings for easy attachment to a couple of screws secured to a wall. Also supplied are 4 adhesive backed rubber feet that can be adhered to the enclosure bottom for table or Mount on a desk top.





