2.3 Inch Four-Digit LED Multifunction Countdown, Count up Timers and Time of Day Clock DC-25UT



Features

- Counts up or down to/from 99 hours
- Displays to 100ths of a sec. Shift Digit Technology
- All aluminum enclosure that mounts to standard electrical 2 x 4 or 4 x 4 junction box
- Factory calibrated
- Flush tactile pushbutton controls mounted on top

Options

- High output end of period buzzer
- Wired handheld remote control
- NEMA 4X IP66, IK08 rated enclosure
- Higher power RF Wireless controls



- Visible up to 120Ft
- Large 2.3-inch bar type super bright LED's
- Made in the USA
- 120Vac w/ ground 3-prong power cord
- LED indicators of timing mode
- Factory Serviceable
- 120 VAC 9 foot power cord
- Tripod mount
- Relay output end of period
- 100s of options call 800-977-6872

Specifications

- Controls
 Tactile pushbutton controls mounted on top of the enclosure: Start/Stop, Reset to last Value, Reset to zero, Clock/Timer, Count up/Countdown, Set Hours, Set Minutes
- **Display** Four digit bar; high intensity; seven segment; red LED display
- Case All aluminum enclosure, 9.625"W x 4.625"H x 3"D
- Weight 4.0 Pounds
- Power Source 3 Watts; 90 240VAC 50/60 Hz, 6ft 3-prong power cord
 - **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- Case Finish Black Textured Powder Coating

DC-25UT Description

The DC-Digital <u>DC-25UT</u> is designed to be used where a universal count up, countdown, timer and time of day clock is needed. The <u>DC-25UT</u> utilizes the **shift digit technology** that allows the user to see hours as well as hundredths of a second. The flexibility of this unique design gives it a broad range of applications in schools, industry, governmental and churches. The tope mounted controls gives the user flexible and instant control at any time . It can be used in either existing buildings or new construction. Long viewing distances are accomplished with its large red LED display. The all aluminum, black extra tuff powder coated enclosure gives it a professional look that will hold up in many harsh environments.

DC-25UT Mounting and Dimensions

There are (6) keyhole mounting knockouts for easy attachment to an electrical handy-box or an electrical 4 square box or simply use the (2) outer keyhole mounting knockouts and a couple of screws secured to a wall. Also supplied are 4 adhesive backed rubber feet that can be adhered to the enclosure bottom for table or Mount on a desk top.

