

6.0 Inch Four-Digit LED Digital
Network NTP, POE, Time of Day
Clock with Surface Mount all Aluminum
Enclosure (OUTDOOR)

DC-60N-POE



Features

- Web page browser-based interface
- User selectable DHCP or Static IP (default DHCP)
- User selectable time zones & time format
- Acquires atomic NTP from any server
- Web page server setup
- Automatically displays it's IP address on power up
- IP-66, All extruded aluminum enclosure
- Sealed and gasketed for waterproofing
- Large 6.0-inch super bright bar LED's
- Visible up to 300 ft. away
- Power Over Ethernet
- Field replaceable led digits
- Made in the USA

Options

- Can be grouped; [DC-Webserver-Clocks-1](#)
- Indoor version
- [NEMA 4X Polycarbonate case](#)
- Wireless system setup
- Green, amber, white LEDs
- 12VDC, 24VDC, 120VAC power available
- Food grade PE, EPDM, PTFE gasketing material
- Customizable [contact us](#)

Specifications

- **Input** POE (Power Over Ethernet), NTP via user selectable server
- **Display** 6 Four-digit outdoor red LED seven segment oval 110 x 45 degree viewing angle; field replaceable digits
- **Case** All extruded aluminum waterproof IP-66 gasketed & sealed enclosure .125" thick, 16.25" W x 7.875"H x 3.250" D
- **Weight** 10.0 Pounds
- **Power Source** PoE Injector Adapter PoE+ Injector 30W 10/100/1000Mbps IEEE 802.3af/at Compliant (INCLUDED)
- **Operating Temp** 0° to 49° Celsius (32° to 120° Fahrenheit)
- **Case Finish** Black textured fingerprint resistant powder coating
- **Cabling** Junction box right side, RJ-45 Cat 5-6 (CE, Fcc compliant)

DC-60N-POE Description

The DC-Digital [DC-60N-POE](#) time of day clock is designed to be used in any application where any 4 digit time of day clock is needed to be seen. It automatically queries NTP time once every 1 minute and on power up (user selectable). It can be set up for 12- or 24-hour time format (default is 12 Hour). It can be set to receive the NTP from your server (default is NIST). This unique design can be used in either existing buildings or new construction. The [DC-60N-POE](#) time of day clock comes with an all extruded waterproof IP-66 aluminum case, and keyhole mounting brackets. This equipment is proudly made in the USA. This display is factory serviceable.

DC-Digital [DC-60N-POE](#) Mounting and Dimensions

(2) Adjustable keyhole mounting tabs for attachment to a supporting structure or wall.

